

---

# INDEX

## A

air compressor intercooler, 85

## B

baffle cut, 32, 37, 38, 40–48, 70, 72, 89, 90, 91, 97, 101, 114, 164, 177, 183, 195  
very small and very large, 37, 38

baffle cut, orientation of

- horizontal cut, 38
- vertical cut, 38, 89, 135

baffle cut, recommended, 38

baffle spacing, 2, 6, 19, 32, 36–39, 41–45, 47, 48–50, 62–65, 70, 72, 77, 90–93, 97, 98, 101, 103–105, 116, 177, 183, 184, 190, 193, 195–198, 200, 201, 203  
maximum baffle spacing, 36  
minimum baffle spacing, 36, 62  
optimum baffle spacing, 37  
variable baffle spacing, 91

baffles

- deresonating, 205, 207
- double-segmental, 38, 47–49, 85, 91, 93, 97, 98, 101, 116, 196, 197, 199, 200
- helical, 1, 211
- rod baffles, 145, 205, 211
- single-segmental, 47–49, 91, 93, 94, 96, 102, 116, 145, 196–199, 201, 203

baffle-shell leakage (see also leakage and bypass streams), 42, 43, 44, 59, 65, 71

boiling

- boiling range, 3, 124, 126, 132, 133, 143, 154
- convective boiling, 127
- critical pressure, 3, 21, 22, 126, 127, 142–144, 157
- critical temperature, 157
- film boiling, 3, 56, 124, 139, 140, 144, 146, 147, 149, 154, 167
- flow boiling, 3, 127

incipient boiling, 125

maximum heat flux, 126, 127, 142, 143, 149, 150

natural convection, 124–126, 213

nucleate boiling, 56, 124, 125, 127, 139,

140, 143, 144, 146–149, 154, 167, 213

pool boiling, 3, 123, 124, 126–128, 132, 133

pool boiling curve, 123, 124

porous surface, 125, 144

rough surface, 125, 176

sintered surface, 125

steady-state film boiling, 124

subcooled liquid heating, 141–143, 152

unsteady-state film boiling, 124

wide-boiling mixture, 127, 131, 132,

135–137, 142, 150, 154

broad objectives of thermal design, 19

## C

channel, 5, 7, 10–13, 23, 64, 68, 71, 112, 127, 141, 221

channel cover, 5, 7, 10, 11, 13, 23, 68

co-current flow (see, flow co-current)

condensation

inside horizontal tubes, 86

inside vertical tubes, 86

of mixed vapors,

outside horizontal tubes, 108

outside vertical tubes, 88

dropwise, 86

film-wise, 86

gravity-controlled, 86, 88, 89, 101

isothermal, 85, 92

shear-controlled, 86, 88, 89, 101

condenser

ejector condenser, 49, 85, 116

reflux condenser, 87, 88

surface condenser, 119, 176, 181

condensers, 2, 3, 4, 49, 83, 86–91, 98, 100,

112, 113, 116, 117, 119, 160, 161, 168, 176, 181, 195, 218  
condensing  
on the shellside, 38, 114, 116  
on the tubeside, 114, 116  
condensing range, 83, 85, 90, 96  
conical head, 12  
conversion of pressure drop to heat transfer, 26, 34, 35, 37, 38, 50, 68, 205, 209, 210, 214, 218, 219, 221  
corrosion allowance, 23  
corrosiveness, 68, 69  
corrugated tubes, 211  
countercurrent flow (see flow, countercurrent)  
critical pressure, 3, 21, 22, 126, 127, 142–144, 157  
critical temperature, 157

## D

dam baffle, 109  
dead spaces, 68, 179, 183, 209, 218, 219  
desuperheating, 3, 85, 90, 104–108, 110, 112, 120, 129, 160  
dry-wall desuperheating, 105, 106  
wet-wall desuperheating, 105, 107  
dummy tubes, 40

## E

enhanced heat transfer, 4, 209–211, 215  
benefits of, 210, 215  
equal outlet temperature, 56, 76, 162  
expansion joint, 13, 14, 114

## F

feed-effluent exchanger, 162  
film boiling – see boiling, film,  
finned tubes, 116, 212  
flooding, 87, 88, 112, 117, 118  
flow  
co-current, 52–54, 139, 205  
countercurrent, 3, 24, 51–54, 57, 71, 77, 205, 211, 215, 221  
laminar, 37, 50, 179, 181, 214  
longitudinal, 36–38, 217, 218  
turbulent, 26, 37, 50, 53, 221  
window, 37, 38, 44, 46, 202  
flow rate  
high flow rate, 12  
low flow rate, 72, 87  
flow regime  
annular flow, 87, 88, 139  
choke flow, 137, 142

churn flow, 139  
mist flow, 139  
slug flow, 88, 139  
flow velocity, 175, 177, 178, 197  
flow-induced vibration  
acoustic vibration, 4, 120, 191, 205–207, 208  
damping, 192, 193  
fluidelastic whirling, 48, 94, 97, 191, 193, 194  
modes of tube failure, 193  
natural frequency of tubes, 190, 192, 194, 199  
tube vibration, 49, 190, 191  
turbulent buffeting, 191–195, 199, 200, 206, 208  
unsupported span, 49, 190, 191, 193–195, 197, 199, 200, 203  
vortex shedding, 191–195, 197, 199, 200, 206, 208  
fouling  
adverse effects of fouling, 171  
bio-fouling, 98  
categories of fouling, 4, 173, 183  
cleanliness factor, 176  
corrosion fouling, 173  
dead spaces, 68, 179, 183, 209, 218, 219  
design guidelines to minimize fouling, 179  
fouling resistance, 4, 22, 26, 43, 72, 106, 118, 165, 168, 171, 174, 176–181, 186, 212, 221  
higher tube pitch, 183  
on-line cleaning, 181  
parameters which affect fouling, 166  
particulate fouling, 173  
selection of fouling resistance, 179  
spare tube bundle, 182  
spare unit, 183  
TEMA fouling resistance, 178  
fouling layer thickness, 4, 180, 181, 185, 186

## H

head  
front head, 10-12  
rear head, 10-12  
heat exchangers  
fixed tubesheet, 13, 23, 35, 40, 75, 113, 131  
floating-head, 7, 10, 14–16, 22, 23, 24, 40  
U-tube, 6, 10, 13, 14, 35, 39, 40, 75, 113  
heat flux, 102, 106, 107, 121, 123–127, 129, 130, 132, 138, 141–143, 145, 148–150,

152, 154  
 heat release profiles, 3, 20, 21, 157, 160  
 heat transfer augmentation, 210, 214  
 heat transfer coefficient  
     condensing, 90, 95, 96, 101, 102, 107,  
         110, 113, 117, 118, 121  
     overall, 26, 30, 31, 51, 53, 57, 62, 89, 95,  
         101, 138, 147, 149, 150, 165–167, 171,  
         176, 177, 184, 205, 210, 212, 217, 218  
 shellside, 6, 38, 40, 44–47, 58, 62, 64, 65,  
     77, 78, 102, 105, 176, 183, 184, 186,  
     202, 212, 218, 219  
 tubeside, 24, 25, 26, 27, 30, 31, 54, 76,  
     106, 113, 142, 153, 176, 211, 212, 214,  
     217  
 heat transfer efficiency, 44, 45, 209  
 helical baffle exchangers, 1, 211  
 helixchangers, 218, 219  
 hybrid heat exchangers, 223  
 hydrogen, 3, 160, 212

## I

impingement plate, 5, 8, 9, 112

## L

lanes  
     pass-partition lane, 7, 13, 30, 36, 39, 40,  
         70  
 leakage and bypass streams  
     baffle hole-tube, 39  
     baffle-shell, 42–45, 59, 61, 65, 71  
     pass partition, 5, 24, 53  
 LMTD, 51–55, 57  
 longitudinal baffle, 9, 10, 33, 135  
 loop seal, 109  
 low-fin tubes, 3, 6, 90, 116–118, 126, 144,  
     211

## M

mean temperature difference  
      $F_t$  factor, 54, 55, 57, 77, 78, 205  
 MTD, 51, 53, 54, 56, 58, 59, 61, 62, 67, 98,  
     99, 101, 105–108, 111–113, 132, 133,  
     135, 137, 139, 142, 150, 154, 157, 161,  
     211, 214, 218  
 multiple shells  
     in parallel, 75, 98  
     in series, 3, 23, 57, 62, 76–78, 98, 99,  
         101, 180  
     in series/parallel, 78, 101  
 multiple shells; 3, 23, 57, 62, 75–78, 90, 98,  
     99, 101, 169, 180

## N

natural convection, 124–126, 213  
 noncondensables, 84–87, 89, 120  
 nozzles, 5, 12, 22, 33, 34, 40, 49, 90, 98,  
     110, 112, 119, 120, 131, 136, 190, 221,  
     222

## O

on-line cleaning, 181  
 overdesign, 3, 27, 162–170, 177  
     on performance, 164, 166–168  
     on surface, 164–169

## P

pass-partition plates, 7, 24  
 physical properties, 3, 21, 25, 26, 39, 86, 90,  
     137, 139, 143, 157–159, 163, 166, 177  
 plate heat exchangers, 212, 220  
 plate-fin heat exchangers ( brazed aluminium  
     heat exchangers), 212, 221  
 Prandtl number, 24, 25, 69, 87  
 pressure drop  
     allowable (permitted), 4, 20, 21, 24, 27,  
         28, 30, 49, 72, 73, 76, 85, 90, 98, 104,  
         110, 116, 119, 180, 195  
     shellside, 2, 3, 10, 23, 35, 36, 38, 42, 43,  
         45–49, 64, 77–79, 91, 92, 94, 97–102,  
         116, 119, 120, 183, 195–201, 203, 205,  
         218, 219  
     tubeside, 23, 26–28, 30, 31, 64, 79, 100,  
         114–116, 119, 164, 170, 180, 214  
     utilization of, 43  
 printed-circuit heat exchangers, 212, 222,  
     223

## R

reboilers  
     exit piping, 137, 142  
     forced-flow, 143  
     horizontal thermosyphon, 33, 134–138  
     internal, 123, 128, 129, 154  
     kettle, 15, 17, 34, 130–133, 135, 136,  
         137, 143, 145  
     selection of reboilers, 153  
     start-up of reboilers, 154  
     static head, 90, 138, 141, 143, 152, 153  
     vertical thermosyphon, 3, 12, 22, 53, 84,  
         88, 136, 138–141, 143, 145, 147, 148,  
         150, 152, 213  
 reduced pressure, 127, 142, 144  
 reflux condensers, 87, 88  
 Reynold's number, 24, 25, 27, 30, 35, 41,  
     68, 69, 70, 86, 87, 121, 192, 213, 214, 221

RODbaffle heat exchangers, 217, 218

## S

seal rods, 40

sealing strips, 5, 8, 9, 40, 41, 164  
shear

vapor shear, 85, 88–90, 95, 110

shell

crossflow shell, 34–36, 38, 49, 55, 119

divided-flow shell, 20, 33, 49, 85, 91, 96–  
98, 119, 198–200, 203

double-split flow shell, 33

single-pass shell, 32, 47, 49, 54, 55, 91,  
96, 97, 196, 199

split-flow shell, 33, 134

TEMA E, 32, 96, 116, 196

TEMA F, 32, 111

TEMA G, 33, 111, 134

TEMA H, 33, 134

TEMA J, 33, 97, 116, 205

TEMA K, 34

TEMA X, 34, 116, 135

two shells in series, 55, 63, 64, 70, 73,  
76–79, 98–100, 102, 104, 110, 167,  
184

sliding strips, 5, 8, 9

spare tubes, 22

specific heat, 22, 24–26, 51, 52–54, 112,  
157, 158, 160, 161

spiral heat exchangers, 179

stepwise calculations, 30

stream analysis, 1, 2, 7, 30, 39–45, 63, 65,  
70, 72, 77, 78, 100–103, 183–186, 217

subcooled boiling, 139

subcooling, 3, 90, 104, 108–112, 168

## T

TEMA, 5–8, 10–12, 14–17, 22, 23, 31–36,  
38, 40, 50, 54–57, 116, 176, 178, 179,  
183, 188, 191, 196–200, 202–205, 208,  
221

temperature cross, 3, 33, 56, 57, 70, 73, 76,  
98, 99, 162, 166, 169, 186, 202, 205, 211,  
220

temperature profile distortion, 2, 3, 32, 41,  
42, 44, 59–65, 71, 77, 78, 184, 185, 217

thermal conductivity, 22, 25, 117, 157, 158,  
160, 181, 212, 221

tube diameter, 24, 25, 27, 39, 68, 69, 85,  
144, 147, 180, 185, 192

tube inserts

twisted-tape inserts, 214

wire-fin, 181, 214, 215, 217

tube layout

tube layout angle, 41, 192, 193, 206, 207

tube layout pattern, 2, 31, 34, 35

tube length, 7, 19, 22–24, 27, 30, 33, 40, 80,  
85, 113, 119, 127–129, 131, 135, 140,  
189, 205, 217

tube pitch, 2, 19, 32, 34, 35, 41, 46, 47, 49,  
50, 69, 120, 127, 183, 192, 194, 207

tubes

bare, 117, 125, 209, 213–216

corrugated, 211

dummy, 40

finned, 212

fluted, 213

high-flux, 125, 143, 144, 211, 213

large diameter tubes, 180

low-fin, 3, 6, 90, 116–118, 126, 144, 211  
tubeside velocity, 24, 26, 27, 30, 76, 119,  
153, 155, 177

twisted, 1, 211

unsupported span, 49, 190, 191, 193–195,  
197, 199, 200, 203

U-tubes, 6, 11, 14, 15, 128, 129, 131, 133,  
135, 191, 194

tubesheet, 5–7, 10–16, 23, 71, 87, 140, 141,  
194, 207

turbulence, 34, 35, 53, 68, 70, 126, 132, 179,  
181, 192, 210–213, 219, 220, 221

twisted-tube heat exchangers, 181, 187, 211,  
219, 220

## U

U-bends, 14, 40, 129

## V

vapor density, 85, 93, 96, 97, 113, 119, 143,  
195

velocity

low, 49, 74, 75, 108, 213, 218

shellside, 6, 37, 43, 49, 62, 65, 75–78, 92,  
99, 102, 177, 183, 184

tubeside, 24, 26, 27, 30, 76, 119, 153,  
155, 177

viscosity, 22, 24–26, 28, 30, 31, 41, 53,  
58, 59, 61, 62, 67–72, 80, 90, 110, 136,  
143, 150, 157–160, 166, 180, 193, 216